

EVVOSEMI[®]

THINK CHANGE DO



ESD




TVS



MOS



LDO



Diode



Sensor



DC-DC

Product Specification

▶ Domestic	Part Number	EV2SC3357-SB
▶ Overseas	Part Number	2SC3357
▶ Equivalent	Part Number	2SC3357


"SB" means SOT-89

EV is the abbreviation of name EVVO

■ NPN Transistors

■ Features

- Low noise and high gain
- High power gain
- Large P_{tot}



■ Simplified outline(SOT-89)

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V_{CBO}	20	V
Collector - Emitter Voltage	V_{CEO}	12	
Emitter - Base Voltage	V_{EBO}	3	
Collector Current - Continuous	I_C	100	mA
Collector Power Dissipation	P_C	1.2	W
Junction to Ambient Resistance	$R_{th(j-a)}$	62.5	$^\circ\text{C}/\text{W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to 150	

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V_{CBO}	$I_C = 100 \mu\text{A}, I_E = 0$	20			V
Collector- emitter breakdown voltage	V_{CEO}	$I_C = 1 \text{ mA}, I_B = 0$	12			
Emitter - base breakdown voltage	V_{EBO}	$I_E = 100 \mu\text{A}, I_C = 0$	3			
Collector-base cut-off current	I_{CBO}	$V_{CB} = 20\text{V}, I_E = 0$			1	uA
Emitter cut-off current	I_{EBO}	$V_{EB} = 3\text{V}, I_C = 0$			1	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 50 \text{ mA}, I_B = 5 \text{ mA}$			0.4	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = 50 \text{ mA}, I_B = 5 \text{ mA}$			1.2	
DC current gain (Note.1)	h_{FE}	$V_{CE} = 10\text{V}, I_C = 20 \text{ mA}$	50		250	
Insertion Power Gain	$ S_{21e} ^2$	$V_{CE} = 10\text{V}, I_C = 20 \text{ mA}, f = 1 \text{ GHz}$		9		dB
Noise Figure	NF	$V_{CE} = 10\text{V}, I_C = 7 \text{ mA}, f = 1 \text{ GHz}$		1.1		
		$V_{CE} = 10\text{V}, I_C = 40 \text{ mA}, f = 1 \text{ GHz}$		1.8	3	
Reverse Transfer Capacitance	C_{re}	$V_{CB} = 10\text{V}, I_E = 0, f = 1 \text{ MHz}$			1	pF
Transition frequency	f_T	$V_{CE} = 10\text{V}, I_C = 20 \text{ mA}$		6.5		GHz


Note.1: Pulse measurement: $PW \leq 350 \mu\text{s}$, Duty Cycle $\leq 2\%$

■ Classification of h_{FE}


Type	2SC3357-F	2SC3357-E
Range	80-160	125-250
Marking	RF	RE

■ Typical Characteristics


TOTAL POWER DISSIPATION
vs. AMBIENT TEMPERATURE




REVERSE TRANSFER CAPACITANCE
vs. COLLECTOR TO BASE VOLTAGE




DC CURRENT GAIN vs.
COLLECTOR CURRENT




GAIN BANDWIDTH PRODUCT
vs. COLLECTOR CURRENT



INSERTION POWER GAIN, MAG
vs. FREQUENCY




INSERTION POWER GAIN
vs. COLLECTOR CURRENT




■ Typical Characteristics


NOISE FIGURE vs.
COLLECTOR CURRENT



IM₂, IM₃ vs. COLLECTOR CURRENT



■ SOT-89



DIMENSIONS (mm are the original dimensions)

UNIT	A	b_{p1}	b_{p2}	b_{p3}	c	D	E	e	e_1	H_E	L_p	w
mm	1.6 1.4	0.48 0.35	0.53 0.40	1.8 1.4	0.44 0.23	4.6 4.4	2.6 2.4	3.0	1.5	4.25 3.75	1.2 0.8	0.13

Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.