



MBR3035PT THRU MBR30100PT

30.0 AMPS. Schottky Barrier Rectifiers



Voltage Range
35 to 100 Volts
Current
30.0 Amperes



Features

- Plastic material used carries Underwriters Laboratory Classifications 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High current capability, low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Guardring for overvoltage protection
- High temperature soldering guaranteed: 260°C/10 seconds, 0.17" (4.3mm) from case

Mechanical Data

- Cases: JEDEC TO-3P/TO-247AD molded plastic body
- Terminals: Leads solderable per MIL-STD-750, Method 2026
- Polarity: As marked
- Mounting position: Any
- Mounting torque: 10 in. - lbs. max
- Weight: 0.2 ounce, 5.6 grams

TO-3P/TO-247AD



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	MBR 3035 PT	MBR 3045 PT	MBR 3050 PT	MBR 3060 PT	MBR 3090 PT	MBR 30100 PT	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	35	45	50	60	90	100	V
Maximum RMS Voltage	V _{RMS}	24	31	35	42	63	70	V
Maximum DC Blocking Voltage	V _{DC}	35	45	50	60	90	100	V
Maximum Average Forward Rectified Current (SEE FIG. 1)	I _(AV)	30						A
Peak Repetitive Forward Current (Rated V _R , Square Wave, 20KHz) at Tc=105°C	I _{FRM}	30.0						A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	250						A
Peak Repetitive Reverse Surge Current (Note 2)	I _{RRM}	2.0		1.0				A
Maximum Instantaneous Forward Voltage at (Note 1) I _F =15A, Tc=25°C I _F =15A, Tc=125°C I _F =30A, Tc=25°C I _F =30A, Tc=125°C	V _F	- 0.60 0.76 0.72		0.75 0.65 - -		0.85 0.75 - -		V
Maximum Instantaneous Reverse Current @ Tc=25°C at Rated DC Blocking Voltage Per Leg(Note 2) @ Tc=125°C	I _R	1.0 60.0				5.0 100.0		mA mA
Voltage Rate of Change at (Rated V _R)	dV/dt	10,000		1,000				V/uS
Maximum Thermal Resistance Per Leg(Note 3)	R θ _{JC}	1.4						°C/W
Operating Junction Temperature Range	T _J	-65 to +150						°C
Storage Temperature Range	T _{STG}	-65 to +175						°C

Notes: 1. 2.0us Pulse Width, $f=1.0\text{ KHz}$

2. Pulse Test: 300us Pulse Width, 1% Duty Cycle

3. Thermal Resistance from Junction to case Per Leg

RATINGS AND CHARACTERISTIC CURVES (MBR3035PT THRU MBR30100PT)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6- TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

